

(19) World Intellectual Property Organization  
International Bureau




(43) International Publication Date  
25 September 2003 (25.09.2003)

PCT

(10) International Publication Number  
**WO 03/078066 A1**

- (51) International Patent Classification<sup>7</sup>: **B01L 3/02**, G01N 35/10, B05B 9/047, 17/06
- (21) International Application Number: PCT/GB03/00431
- (22) International Filing Date: 31 January 2003 (31.01.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
02251774.2 13 March 2002 (13.03.2002) EP  
60/394,262 9 July 2002 (09.07.2002) US
- (71) Applicant (*for all designated States except US*): **THE AUTOMATION PARTNERSHIP (CAMBRIDGE) LIMITED** [GB/GB]; York Way, Royston, Hertfordshire SG8 5WY (GB).
- (72) Inventor; and
- (75) Inventor/Applicant (*for US only*): **BARGH, Adrian, Neil** [GB/GB]; 84 South View Road, London N8 7LS (GB).
- (74) Agent: **GILL JENNINGS & EVERY**; Broadgate House, 7 Eldon Street, London EC2M 7LH (GB).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:  
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(54) Title: LOW VOLUME DROPLET DISPENSING



(57) Abstract: A low volume dispensing apparatus has a droplet dispensing assembly (5) having a cylinder (51) for containing a fluid to be dispensed and having a nozzle (2) at one end. Extending through the other end is a piston (52, 54). A driving device (8) is connected to the piston and cylinder to move the piston relatively outwardly or inwardly along the cylinder to draw fluid into the cylinder through the nozzle or to provide fluid to the nozzle for dispensing therefrom. An impulse driver (7) connected to the droplet dispensing assembly or to the driving device to dispense fluid from the cylinder through the nozzle in a pulsed manner. A sensor (102) may be used to sense the position of the dispensing apparatus relative to the individual wells (100) in a sample plate (104) into which liquid is to be dispensed.

BEST AVAILABLE COPY

WO 03/078066 A1

dispensing by the impulse driver respectively. The driving device may be connected to the supply channel to supply fluid to the cylinder in use.

5 A valve may be disposed between the nozzle and the piston, movable between a first position in which the supply channel is in communication with that part of the cylinder between the valve and the piston and a second position in which the supply channel is closed and that part of the cylinder between the valve and the piston is in communication with the nozzle. Preferably a fluid reservoir is connected to the supply channel.

10 The impulse driver may comprise a piezoelectric actuator, a pneumatic actuator, a solenoid actuator or the like.

The driving device may include a screw-thread drive or other step-less drive.

A seal is preferably provided between the piston and the cylinder.

15 The apparatus may include a plurality of droplet dispensing assemblies, wherein the cylinders of the dispensing apparatus are connected to a common manifold for fluid to be dispensed and the pistons extend through the manifold. The manifold may be connected to a supply line which is selectively engageable with the manifold.

According to a further aspect of the invention there is provided a low volume dispensing apparatus including

20 a droplet dispensing assembly arranged to be moved transversely across a sample plate having a plurality of wells or micro-tubes and to dispense droplets of liquid into the wells or micro-tubes;

25 a sensor positioned adjacent the droplet dispensing assembly and arranged to sense the location of the wells or micro-tubes or the dividing walls or the like therebetween and to provide a trigger signal indicative thereof; and

a circuit for actuating dispensing by the droplet dispensing assembly on receipt of the trigger signal.

Examples of devices constructed in accordance with the present invention will now be described with reference to the accompanying drawings in which:-

30 Figure 1 illustrates, diagrammatically, a first example of a dispensing apparatus;

Figure 2 illustrates stages in the operation of the first example;

Figure 3 illustrates a second example;

Figure 4 illustrates a modified version of the second example;

Figure 5 illustrates another modified version of the second example;

35 Figure 6 illustrates a further modified version of the second example;

Figures 7A and 7B illustrate stages in the operation of the modified example;

seat 75 and the piston rod head 55 being accurately controlled by the screw-thread drive 8 (Figure 2B).

To cause the dispensing of a precisely controlled amount liquid from the pipetting nozzle 2, the drive rod 73 is moved rapidly upwards between the position shown in Figure 2B and the position shown in Figure 2C, to drive the piston rod 54 upwards, until the piston rod head 55 re-engages the seat 75 and in so doing, as will be appreciated by referring to Figure 1, moving the piston 52 upwards and driving liquid from the liquid volume 53, through the three way valve 6 and the tube 3 and out of the end of the pipetting nozzle 2. The impulse drive piston 72 is then retracted to the start position as is shown in Figure 2D and the screw-thread drive 8 then moves the support 81 upwards, effectively lowering the piston rod head 55 inside the impulse drive unit 7, to allow another dispense cycle to be initiated.

It will be appreciated that a combination of the screw drive 8, which, in effect, provides a driving device to control the amount of liquid in the liquid volume 53 by either drawing it in to the volume 53 from the reservoir 1 or else (if desired) moving it back to the reservoir 1, and by using it to fix the distance of travel of the piston rod 54, very accurate control of the amount of liquid dispensed can be achieved.

Figure 3 illustrates a second example in which liquid to be dispensed is drawn directly into a pipetting nozzle or needle 2 by dipping the needle 2 into the liquid. In this example, the pipetting nozzle 2 has a cylindrical wall 21 which contains, as a close fit a piston 22. The piston may carry a piston seal (not shown) or else a seal may be provided at the top end (as shown in the figure) of the cylindrical wall 21, engaging the side of a piston rod 23 which is connected to the piston 22. At the opposite end of the piston rod 23 a piston rod head 24 is located within an impulse drive unit 7 which is substantially the same as that shown in Figures 1 and 2 and which operates in a substantially identical fashion and which is again carried by a screw-threaded drive 8.

In a modification of the Figure 3 example, shown in Figure 4, the impulse drive unit of Figure 3 is replaced with a impulse drive unit 7 which includes a piezoelectric actuator 76 having a head 24 which is connected to the piston rod 23, the actuator 76 being biased by a coil spring 77 away from the seat 75. Actuation of the piezoelectric actuator 76 drives the piston 22 to dispense a droplet as before. The coil spring 77 maintains the actuator 76 in contact with the piston rod head 24.

In a further modification of the Figure 4 example, shown in Figure 5, the piezoelectric actuator 76 is directly connected to the head 24 of the piston rod 23.

In a further modification of the Figure 3 example, shown in Figure 6, fluid is supplied to the pipetting nozzle 2 via a supply conduit 90 connected to a port 91 of the

into the manifold 9 and hence into the pipetting nozzles 2 and thereafter the pistons 22, 23 are inserted through the tops of the pipetting nozzles 2 by the action of the screw-thread drive 8. The impulse drive unit 7 can then be operated as before, in order to cause predefined amounts of liquid to be dispensed from the plural pipetting nozzles either for dispensing of a liquid reagent or for washing purposes as illustrated in Figure 9B.

Figure 10 illustrates a still further example, similar to that of Figure 8, but in which, instead of impacting the piston 22 within each pipetting nozzle 22 the pipetting nozzles are mounted on a carriage 27 which is supported against the bias of a spring 28 within a support 29 and the impulse drive unit 27 plural pistons 72 and cylinders 71 with associated drive rods 73 which are caused to impact against the carriage 27 to cause liquid to be dispensed through the pipetting nozzles 2.

Figure 11 illustrates a further modification of the example shown in Figure 3, in which, additionally, an optical (eg infra-red) sensor 102 is used to locate the position of dividing walls 101, which separate individual wells 100 in a sample plate 104 into which liquid is to be dispensed from the pipetting nozzle 2 of the apparatus as the nozzle 2 is moved over the wells 100, and to provide a trigger signal to a circuit 103 to actuate the impulse driver 7 to cause a droplet to be dispensed into the adjacent well 100. This is useful to overcome the tolerances or variations which occur in the size and spacing of the wells 100 (or micro-tubes) in a typical micro-titre sample plate, by sensing the positions of the dividing walls or the like and relating this to the position of the nozzle 2 to trigger dispensing into the adjacent well 100, rather than relying on the spacing between wells being absolutely uniform and advancing the nozzle across the sample plate in a series of fixed steps at each of which a droplet is dispensed.

A similar sensor may be used in connection with any of the examples shown above.

wherein the driving device is connected to the supply channel to supply fluid to the cylinder in use.

- 5 8. Apparatus according to any of claims 1 to 7, further including a valve disposed between the nozzle and the piston, and movable between a first position in which the supply channel is in communication with that part of the cylinder between the valve and the piston and a second position in which the supply channel is closed and that part of the cylinder between the valve and the piston is in communication with the nozzle.
- 10 9. Apparatus according to claim 6, or to claim 7 or claim 8 when dependent on claim 6, further including a fluid reservoir connected to the supply channel.
- 15 10. Apparatus according to any of claims 1 to 9, wherein the impulse driver comprises a piezoelectric actuator.
11. Apparatus according to any of claims 1 to 9, wherein the impulse driver comprises a pneumatic actuator.
- 20 12. Apparatus according to any of claims 1 to 9, wherein the impulse driver comprises a solenoid actuator.
13. Apparatus according to any of claims 1 to 12, wherein the driving device includes a screw-thread drive.
- 25 14. Apparatus according to any of claims 1 to 13, further including a seal between the piston and the cylinder.
- 30 15. Apparatus according to any of claims 1 to 14, having a plurality of droplet dispensing assemblies, wherein the cylinders of the dispensing apparatus are connected to a common manifold for fluid to be dispensed and the pistons extend through the manifold.
16. Apparatus according to claim 15, wherein the manifold is connected to a supply line.

35




Fig 1

3/11




Fig 3

BEST AVAILABLE COPY

5/11




Figure 5

BEST AVAILABLE COPY






Figure 7B

Figure 7A




Figure 9B

Figure 9A




Figure 11

## INTERNATIONAL SEARCH REPORT

International Application No

PL, GB 03/00431

C(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 97 16251 A (TECAN AG) 9 May 1997 (1997-05-09) cited in the application the whole document ----	1,10-14
X	US 6 112 605 A (MEYER WILHELM ET AL) 5 September 2000 (2000-09-05) column 2, line 41 -column 2, line 51 column 3, line 38 -column 5, line 3 column 5, line 62 -column 6, line 37 column 7, line 4 -column 8, line 7 column 8, line 48 -column 8, line 57 figure 1 ----	1,10-17
X	EP 1 093 856 A (TECAN SCHWEIZ AG) 25 April 2001 (2001-04-25) paragraphs '0007!', '0013!'-'0017! figure 3 ----	1,10-14
E	EP 1 206 966 A (TECAN TRADING AG) 22 May 2002 (2002-05-22) abstract the whole document ----	1-5, 10-17
X	DE 28 45 638 A (WALZEL PETER DR ING) 30 April 1980 (1980-04-30) page 3, line 1 -page 3, line 20 ----	1
X	US 6 203 759 B1 (MEYER WILHELM ET AL) 20 March 2001 (2001-03-20) column 12, line 38 -column 13, line 13 ----	1,10-18
A	US 5 104 621 A (PFOST DALE R ET AL) 14 April 1992 (1992-04-14) column 13, line 5 -column 13, line 13 figure 2 column 5, line 50 -column 6, line 40 column 10, line 1 -column 13, line 4 ----	18
A	US 5 529 754 A (BONACINA GUIDO ET AL) 25 June 1996 (1996-06-25) abstract ----	18
A	DE 199 23 222 A (BIOTUL AG I K) 7 December 2000 (2000-12-07) claims 1,2 column 1 -----	18

## INTERNATIONAL SEARCH REPORT

Int. Patent Application No

PCT/GB 03/00431

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 6203759	B1	20-03-2001	US 6521187 B1	18-02-2003
			US 6537817 B1	25-03-2003
			US 2001014477 A1	16-08-2001
			US 2001016177 A1	23-08-2001
			EP 0810438 A2	03-12-1997
			JP 10114394 A	06-05-1998
			US 6083762 A	04-07-2000
			US 6079283 A	27-06-2000
			US 5927547 A	27-07-1999
			US 6094966 A	01-08-2000
			US 6112605 A	05-09-2000
			US 6220075 B1	24-04-2001
			AU 6963798 A	30-10-1998
			EP 1007973 A2	14-06-2000
			WO 9845205 A2	15-10-1998
US 5104621	A	14-04-1992	US 5139744 A	18-08-1992
			US 5108703 A	28-04-1992
			EP 0261202 A1	30-03-1988
			FI 875113 A	19-11-1987
			JP 8082630 A	26-03-1996
			JP 8054401 A	27-02-1996
			JP 63502931 T	27-10-1988
			WO 8706008 A2	08-10-1987
			US 5125748 A	30-06-1992
			US 5206568 A	27-04-1993
			US 5369566 A	29-11-1994
US 5529754	A	25-06-1996	AT 206212 T	15-10-2001
			DE 59509629 D1	31-10-2001
			EP 0681184 A1	08-11-1995
			ES 2164116 T3	16-02-2002
			JP 2799302 B2	17-09-1998
			JP 8043404 A	16-02-1996
DE 19923222	A	07-12-2000	DE 19923222 A1	07-12-2000